AC Plus Radiata

SANDED PLYWOOD







Roseburg's AC Plus Radiata pine plywood is a lightweight, strong and durable sanded plywood panel produced with a multi-layered western softwood core and A Grade Radiata pine face. When you combine the natural beauty of real wood and the manufacturing quality of Roseburg, you get one of the finest plywood panels offered on the market today.



AC Plus Radiata

SANDED PLYWOOD

TECHNICAL DATA				
Length	8'			
Width	4'			
Thicknesses	1/4, 11/32, 15/32, 19/32, 23/32			
Face	A Grade Radiata pine			
Core	Western softwood C grade			
Back	Western softwood C			
Adhesive	Water-resistant no added urea formaldehyde (NAUF) phenolic resin			
Face Finish	Finish sand			

DACK		C D		11 C
PA(K	AGIN	(-, 1)	$\mathbf{F} \mathbf{I} \mathbf{\Delta}$	
		\smile		

Thickness (in)	Pieces Per Unit	#/MSF	#/Unit
1/4 (3 ply)	120	725	2,785
11/32 (3 ply)	90	950	2,750
15/32 (5 ply)	33	1,350	1,376
19/32 (5 ply)	53	1,600	2,715
23/32 (7 ply)	44	1,900	2,860

FEATURES AND BENEFITS

- Exceptional strength and stiffness for a wide range of applications
- Meets the Engineered Wood Association (APA) criteria for sanded and underlayment panels

COMMON APPLICATIONS

- · Interior wainscoting
- Moisture-protected exteriors such as soffits and porch ceilings
- Furniture
- · Cabinets
- Shelving
- Bookcases

STANDARDS AND CERTIFICATIONS

• Meets APA PS 1-19









